

# → FGM-700

NS-GX1-300 Network Appliance



## Features

- Ultra Low Power NS GX1-300 MHz CPU
- Support 4 x Realtek 8139C 10/100 Mbps Fast Ethernet
- Support PC-100 SO-DIMM Socket up to 512MB
- Aluminum Frame

## Specifications

### System

- Form Factor : Network Appliance
- CPU : Ultra Low Power NS GX1-300 MHz CPU
- Memory : 1x 144-pin SO-DIMM Socket up to 512MB SDRAM
- Chipset : CS5530A Chipset
- LAN : 4 x Realtek 8139C 10/100 Fast Ethernet
- Expansion Bus : 1 x Mini PCI Socket
- 1 x 32bit/33Mhz PCI Slot

### Storage

- SSD / Drive : 1 x Compact Flash Disk socket

### Front Panel

- Red LED for Power Status
- Twelve LED for 4 x RJ45 LAN Operating Status

### External I/O

- KB/MS : 1 X PS2 K/B and Mouse
- Display : 1 X DB15
- USB Port : 2 X USB 1.1 Compliant
- Serial Port : 1 X DB9
- LAN Port : 4 X RJ45

### Power Adapter

- AC Input : 100 ~ 240V, 50 ~ 60Hz
- DC Output : 16W, +12V@1.25A

**ANNSO TECHNOLOGY CO., LTD**

Factory address: Hexi District of JinXia, Chang'an Town, Dongguan City, Guangdong, China.  
Tel: +86-769-5387700 5387755 5305389 5305396 5531482 5530279 Fax: +86-769-5329662



## Mechanical & Environmental

- Operating Temperature : 0°C ~ 45 °C
- Storage Temperature : -20°C ~ 60 °C
- Operating Humidity : 5% ~ 95%, non condensing
- Dimension (W x H x D) : 210 x 47 x 168mm (8.3" x 1.85" x 6.6")
- Weight : 3.9 kg

## Ordering Information

- **FGM-700**  
NS GX1-300 Network Appliance with 4 x Fast Ethernet, AC-DC Power adapter +12v@1.25A
- **FGM-700-B**  
NS GX1-300 Network Appliance with 4 x Fast Ethernet, AC-DC Power adapter +12v@1.25A

## Dimension Diagram

unit:mm

