

1+1 Console 8/16/32 Port *Cat5* Combo17" LCD KVM

KVM-17ASL

| | | | |
|--|--|-----------------|-------------|
| LEDs / Port | 8 | 16 | 32 |
| Power | 1 | | |
| Computer Connections | 8 | 16 | 32 |
| Maximum Computer Connections | 232 | 240 | 256 |
| Computer Connectors | RJ-45 Connector | | |
| Console Ports | 1 (One Local), plus 1Optional Modules : Selectable CAT5-Based or IP Remote Console | | |
| CAT5-Based Remote Console (DCC-150/300) | 1 x RJ-45 connector up to 300 Meters (1000 feet) with CAT5 cable; Remote receiver support 1 x VGA (up to 1280x1024 resolution) 2 x USB for KB & Mouse , 1 x KVM port for connecting an extra PC | | |
| IP-Based Remote Console Module (DIP-101) | 1 x RJ-45 connector for 10/100M Ethernet (remote console up to 1600x1200 resolution), 1 x DB-9 male connector for Modem ,Null Modem and serial power control ,1 x mini USB 2.0 receptacle | | |
| Daisy Chaining | Daisy Chainable up to 8 levels ; Connector : DB-15 (female type) | | |
| Computer Selection | On Screen Display (OSD) , Hot Key , Push Button | | |
| Hotkey | Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win) | | |
| Auto-Scan Intervals | 5 ~ 99 Sec. | | |
| Keyboard / mouse Emulation | PS/2 | | |
| Video Resolution (Local Console) | 1024 x 768 for 15" , 1280 x 1024 for 17" and 19" | | |
| Video Resolution (Remote Console) | 1280x1024 for CAT5-Based 500 feet remote console ; 1024 x 768 for CAT5-Based 1000 feet remote console ; 1600 x 1200 for IP-Based remote console | | |
| Power Adapter | AC 100-240V , 50/60Hz , DC 12V / 4A , 48w via IEC type cord | | |
| Housing | Metal | | |
| Size | 19" Rack mount , 1U | | |
| Net / Gross Weight (KG) | 16kg / 21kg | 16.5kg / 21.5kg | 17kg / 22kg |
| Physical Dimensions (W x H x D) | 448 x 42 x 580 (mm) | | |
| Packing Dimensions (W x H x D) | 580 x 200 x 790 (mm) | | |
| Operating Temperature | 0 °C to 50 °C | | |
| Storage Temperature | -20°C to 60°C | | |
| Humidity | 10% to 90%,non-condensing | | |
| Certificated | CE/FCC | | |

1+1 Console 8/16/32 Port Cat5 Combo 17" LCD KVM

KVM-17ASL

Order Information

| | |
|--------------------|---|
| KVM-1708ASL | 1U Rack mount 17" TFT LCD W / 8 port Cat5 KVM switch , W/ 48 W power supply |
| KVM-1716ASL | 1U Rack mount 17" TFT LCD W / 16 port Cat5 KVM switch , W / 48 W power supply |
| KVM-1732ASL | 1U Rack mount 17" TFT LCD W / 32 port Cat5 KVM switch , W / 48 W power supply |
| OMI-KIT | One man installation kit |

Dimension Diagram

