



# 1+1 Console 8/16/32 Port *Cat5* Combo19" LCD KVM

## KVM-19ASL

<b>LEDs / Port</b>	8	16	32
<b>Power</b>	1		
<b>Computer Connections</b>	8	16	32
<b>Maximum Computer Connections</b>	232	240	256
<b>Computer Connectors</b>	RJ-45 Connector		
<b>Console Ports</b>	1 ( One Local ), plus 1Optional Modules : Selectable CAT5-Based or IP Remote Console		
<b>CAT5-Based Remote Console ( DCC-150/300 )</b>	1 x RJ-45 connector up to 300 Meters ( 1000 feet ) with CAT5 cable; Remote receiver support 1 x VGA ( up to 1280x1024 resolution ) 2 x USB for KB & Mouse , 1 x KVM port for connecting an extra PC		
<b>IP-Based Remote Console Module (DIP-101)</b>	1 x RJ-45 connector for 10/100M Ethernet ( remote console up to 1600x1200 resolution ), 1 x DB-9 male connector for Modem ,Null Modem and serial power control ,1 x mini USB 2.0 receptacle		
<b>Daisy Chaining</b>	Daisy Chainable up to 8 levels ; Connector : DB-15 ( female type)		
<b>Computer Selection</b>	On Screen Display ( OSD ) , Hot Key , Push Button		
<b>Hotkey</b>	Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)		
<b>Auto-Scan Intervals</b>	5 ~ 99 Sec.		
<b>Keyboard / mouse Emulation</b>	PS/2		
<b>Video Resolution (Local Console)</b>	1024 x 768 for 15" , 1280 x 1024 for 17" and 19"		
<b>Video Resolution (Remote Console)</b>	1280x1024 for CAT5-Based 500 feet remote console ; 1024 x 768 for CAT5-Based 1000 feet remote console ; 1600 x 1200 for IP-Based remote console		
<b>Power Adapter</b>	AC 100-240V , 50/60Hz , DC 12V / 4A , 48w via IEC type cord		
<b>Housing</b>	Metal		
<b>Size</b>	19" Rack mount , 1U		
<b>Net / Gross Weight ( KG )</b>	17.5kg / 21.5kg	17.5kg / 21.5kg	18kg / 22kg
<b>Physical Dimensions ( W x H x D)</b>	448 x 42 x 580 (mm)		
<b>Packing Dimensions ( W x H x D)</b>	580 x 200 x 790 (mm)		
<b>Operating Temperature</b>	0 °C to 50 °C		
<b>Storage Temperature</b>	-20°C to 60°C		
<b>Humidity</b>	10% to 90%,non-condensing		
<b>Certificated</b>	CE/FCC		

# 1+1 Console 8/16/32 Port Cat5 Combo 19" LCD KVM

**KVM-19ASL**

## Order Information

<b>KVM-1908ASL</b>	1U Rack mount 19" TFT LCD W / 8 port Cat5 KVM switch , W/ 48 W power supply
<b>KVM-1916ASL</b>	1U Rack mount 19" TFT LCD W / 16 port Cat5 KVM switch , W / 48 W power supply
<b>KVM-1932ASL</b>	1U Rack mount 19" TFT LCD W / 32 port Cat5 KVM switch , W / 48 W power supply
<b>OMI-KIT</b>	One man installation kit

## Dimension Diagram

