



- |                 |                         |                         |           |
|-----------------|-------------------------|-------------------------|-----------|
| 1. OSD button   | 3. DC Jack              | 5. TouchScreen USB Port | 7. VGA-IN |
| 2. Power Switch | 4. TouchScreen COM Port | 6. Audio-in             | 8. DVI-IN |

### System

- Compact 19" Rack mount TFT LCD monitor, 8U High
- Construction: Heavy duty steel chassis
- Input signal: VGA & DVI , AV IN ( optional )
- Control: Front panel OSD Control
- Power Supply: External 48W DC 12V power adapter
- DC 7V-28V wide range input (optional )
- OS Support: MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
- 90° tilt adjustment while mounted in rack: +45° ~-45° ( V )
- Dimensions (W x H x D): 482.6x355x60mm
- Packing Dimension: 610x490x195
- NET weight: 8.2 KG
- Gross weight: 11.0KG
- Signal Connector: 17 Pin mini D-SUB & DVI , AV connector ( optional )
- Function Control: Power Switch, Menu, Select (+,-), Auto
- OSD: Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
- Touch screen ( optional )
- Speaker : 2x2 W Stereo internal speaker

### LCD

- Display Type : 17" SXGA TFT LCD
- Resolution : 1280 × 1024
- Max.color : 16.7M
- Luminance : 300 cd/m<sup>2</sup>

- View Angel : 178°(H) , 178°(V)
- Pixel Pitch : 0.264 x 0.264 mm
- Contrast Ratio : 1000 : 1
- Response Time : 5 ms
- Power Consumption : 21.9 W
- LCD MTBF : 50,000hrs

### Touchscreen(optional)

- Internal USB or RS-232 interface controller
- Type: Analog resistive type : 25VDC ≥ 20MΩ
- Resolution: continuous
- Light transmission: 80% or more
- Power consumption:<5V @1mA
- Surface hardness : 3H
- Operating force : ≤100g
- Life expectancy : 35 Million
- Operation system : Window 98 / 2000 / ME / XP / NT / CE, DOS , Linux

### Environmental

- Operating temperature: 0°C to 45°C ( 32°F ~ 113°F )
- Storage temperature:-20°C to 60°C (-4°F ~ 140°F )
- Storage humidity: 10% to 95%@ 40°C ,non-condensing,
- Vibration: 10 ~ 170Hz, 0.17mm 10 cycles 1G
- Shock: 30G peak acceleration (11 msec. duration)

## Ordering Information

<b>RMB-17</b>	17" TFT LCD, 48W DC 12V Power Adapter
<b>RMB-17T</b>	17" TFT LCD, Resistive Touchscreen, 48W DC 12V Power Adapter
<b>RMB-17A</b>	17" TFT LCD, 48W DC 12V Power Adapter , w / AV IN Connector
<b>RMB-17TA</b>	17" TFT LCD, Resistive Touchscreen, 48W DC 12V Power Adapter , w / AV IN Connector
<b>RMB-17-DC</b>	17" TFT LCD, DC 7-28V IN Power Module
<b>RMB-17T-DC</b>	17" TFT LCD, Resistive Touchscreen, DC 7-28V IN Power Module
<b>RMB-17A-DC</b>	17" TFT LCD, DC 7-28V IN Power Module, w / AV IN Connector
<b>RMB-17TA-DC</b>	17" TFT LCD, Resistive Touchscreen, DC 7-28V IN Power Module , w / AV IN Connector

## Dimension Diagram

