



Intel / AMD / VIA CPU Compatible, with 2xPCI expansion slot

Features

- 15" XGA TFT LCD Panel
- Support MINI-ITX form factor main board
- High performance PC up to Pentium 4
- Expansion slot 2 x PCI
- Space for 2.5" HDD x 1
- Space for slim optical driver x 1
- AC 115-240V wide range power input
- NEMA4 / IP 65 compliant front panel
- Panel mounting with clip
- Meet standard VESA hole (75x75 and 100x100 mm), support desk top stand / wall mount / swing arm mounting

Optional

- Wireless LAN
- Touch Screen
- 150W ATX power supply
- Open frame structure

Specifications

Mainboard	Space for standard MINI-ITX main board
Processors	Intel / AMD / VIA
Memory	Upgradable standard SDRAM / DDR /DDR2 memory
HDD	Space for 2.5" x 1
Optical Device	Space for Slim CDROM/DVDROM/Combo(DVD+CDRW)DVD±RW
Display	Display Type : 15" XGA TFT LCD Resolution : 1024 × 768 Max.color : 16.2M Luminance : 250 cd/m2 View Angel : 150°(H) , 135°(V) Pixel Pitch : 0.297 x 0.297 mm Contrast Ratio : 700 : 1 Response Time : 8 ms Power Consumption : 11.27 W LCD MTBF : 50,000hrs
Expansion Slots	2 x PCI slot
System Fan	2 x (60x60x10mm) cooling fan
Speaker	Built-in 2x stereo speakers(2w)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Wireless LAN (optional)	usb Interface,Support 64 and 128 bit WEP Encryption *802.11b:11Mbps Up to 180m(Outdoor), 35- 60 m(Indoor) *802.11g:54Mbps up to 50m(Outdoor),20m(Indoor)
Touch Screen (optional)	Internal USB or RS-232 interface controller Type: Analog resistive type : 25VDC ≥ 20MΩ Resolution: continuous Light transmission: 80% or more Power consumption:<5V @1mA Surface hardness : 3H Operating force : ≤100g

	Life expectancy : 35 Million Operation system : Window 98 / 2000 / ME / XP / NT / CE, DOS , Linux
Power Supply	Input: 115~240VAC,50/60Hz Output: ATX 350W with active PFC +5V@ 20 A , +12V@ 16A
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 90%non-condensing Vibration: 17 to 500HZ 1G PTP Shock: 1G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	With front panel: 436 x 313 x 116 mm Without front panel: 430mm x 307mm x 111 mm
Weight (kgs)	Net : 10.5 Gross : 11.6KG

Ordering Information

IPPC-1542-350X	15" Industrial Panel PC Platform , with 350W Power Supply
IPPC-1542RTU-350X	15" Industrial Panel PC Platform with touch screen and USB controller, with 350W Power Supply
IPPC-1542RTC-350X	15" Industrial Panel PC Platform with touch screen and RS-232 controller, with 350W Power Supply
OPPC-1542-350X	15" Open Frame Panel PC Platform , with 350W Power Supply
OPPC-1542RTU-350X	15" Open Frame Panel PC Platform with touch screen and USB controller, with 350W Power Supply
OPPC-1542RTC-350X	15" Open Frame Panel PC Platform with touch screen and RS-232 controller, with 350W Power Supply
AX-150X	150W ATX Power Supply

Dimension Diagram

