



1. OSD Menu

3. RS232

5. AUDIO IN

7. DVI

2. Power Switch

4. USB

6. VGA

Features

- Foldable 1 U height rack-mounting design
- Construction: Heavy-duty steel
- Wide viewing angle
- OSD (On Screen Display) function
- Optional resistive touch screen function

Specifications

- Front panel protection: Hardness Glass
- Construction chassis: Heavy-duty steel
- Input signal: VGA or DVI
- Console ports: 1
- Power Supply: 100-240VAC Input
- OS Support: MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
- Dimensions (W x H x D) : 480x44.4x500mm
- Packing Dimension:
- NET weight:
- Gross weight:
- OSD: Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
- Touch screen (optional)
- Speaker : 2x2W internal stereo speaker
- Operation Temperature: 0~50°C

LCD

- Display Type : 17" SXGA TFT LCD
- Resolution : 1280 × 1024
- Max. color : 16.7M
- Luminance : 300 cd/m2
- View Angel : 178°(H) , 178°(V)
- Pixel Pitch : 0.264 x 0.264 mm
- Contrast Ratio : 1000 : 1
- Response Time : 5 ms
- Power Consumption : 21.9 W
- LCD MTBF : 50,000hrs

Touchscreen(optional)

- Internal USB or RS-232 interface controller
- Type: Analog resistive type : 25VDC ≥ 20MΩ
- Resolution: continuous
- Light transmission: 80% or more
- Power consumption:<5V @1mA
- Surface hardness : 3H
- Operating force : ≤100g
- Life expectancy : 35 Million
- Operation system : Window 98 / 2000 / ME / XP / NT / CE, DOS , Linux

Ordering Information

RMD-17	1U Height 17" Foldable LCD Monitor ,VGA input
RMD-17T	1U Height 17" Foldable LCD Monitor W/Resistive Touch screen , VGA input
RMD-17D	1U Height 17" Foldable LCD Monitor ,DVI input
RMD-17DT	1U Height 17" Foldable LCD Monitor W/Resistive Touch screen , DVI input

Dimension Diagram

