


# CBP - 10P4 REV : A0

Dimensions : 260.16 \* 220.98 mm



# CBP - 10P4 REV : A0

## 1 . CONNECTORS

CONNECTOR	Description
ISA 1~2	PICMG connectors
ISA 3~6	16 BIT ISA BUS connectors
PCI 1~4	32 BIT PCI BUS connectors
P1	Terminal power connector (+/-5V, +/-12V,GND)
CN1	4-PIN ATX P/S connector
CN2	2-PIN +5V DC power controller for ATX power
KB1	To CPU CARD K/B connector
KB2	External K/B connector
AT	To AT power connector
ATX	To ATX power connector
FAN 1~3	3-PIN +12V DC power connector for fan

PCI Slot	IDSEL	PCI Interrupt Pin Route			
		INTA	INTB	INTC	INTD
PCI1	AD31	INTB	INTC	INTD	INTA
PCI2	AD30	INTC	INTD	INTA	INTB
PCI3	AD29	INTD	INTA	INTB	INTC
PCI4	AD28	INTA	INTB	INTC	INTD

CN2	
Don't Care	AT power connector P8/P9
OPEN	ATX power off
CLOSED	ATX power on

\*

**Default : \***

## 2 . PIN Assigement

Keyboard	
PIN	Name
1	KB_CLK
2	KB_DT
3	NC
4	GND
5	+5V

P1	
PIN	Name
1	-5V
2	+5V
3	-12V
4	+12V
5	GND

FAN 1~3	
PIN	Name
1	NC
2	+12V
3	GND

CN1	
PIN	Name
1	PWR_OK
2	5VSB
3	PS_ON
4	GND

CN2	
PIN	Name
1	PS_ON
2	GND

ATX			
PIN	Name	PIN	Name
1	+3.3V	11	+3.3V
2	+3.3V	12	-12V
3	GND	13	GND
4	+5V	14	PS-ON
5	GND	15	GND
6	+5V	16	GND
7	GND	17	GND
8	NC	18	-5V
9	5VSB	19	+5V
10	+12V	20	+5V

AT	
PIN	Name
1	NC
2	+5V
3	+12V
4	-12V
5	GND
6	GND
7	GND
8	GND
9	-5V
10	+5V
11	+5V
12	+5V